

CUBE STRAIGHT

SURFACE & PENDANTS



IP20

ES


Luminaria realizada en extrusión de aluminio. Disponible para lámpara dicróica o LED de Ø50mm.

EN

Recessed spotlight. Made of extruded aluminium. Available for Ø50mm, dichroic lamp or LED.

FR

Luminaire en extrusion d'aluminium. Pour 1 ampoule dycroïque ou LED de Ø50mm.



850°

CUBE STRAIGHT

LED		230V	≈ 6W	> 600lm	CBES A 06 . . . 4 . ..
			≈ 10W	> 1000lm	CBES A 10 . . . 4 . ..
	PAR 16		230V GU 10	50W	CBES E 50 X X X X ..

McAdam C3 · >50.000 h. L90 / CRI >80

DOWNLOAD COMPLETE TECHNICAL DATA AND FILES ON:
ONOKLIGHTING.COM/EN/CUBE-STRAIGHT

INFORMATION ABOUT PACKING SEE PAGE 324

LED CONTROL

	N	No Dimmable	CBES A .. N
	C	Dimmable IGBT / Triac	CBES A .. C
	F	Dimmable 1-10V / Push	CBES A .. F

LED COLOUR TEMPERATURE

	3	3000° K	CBES A .. . 3
	4	4000° K	CBES A .. . 4

LED BEAM ANGLE

	4	Medium	CBES A 4 . ..
--	----------	--------	-------------------------------

LED COMPLEMENTS

	B	Clear Diffuser	CBES A B ..
--	----------	----------------	-----------------------------

COLOURS

	WS	Satin White	CBES WS
	BS	Satin Black	CBES BS
	AL	Aluminium	CBES AL